

<b>Requested document:</b>	<b><a href="#">JP3158236 click here to view the pdf document</a></b>
----------------------------	--

## LAMINATE WITH FLEXIBILITY

Patent Number: JP3158236  
Publication date: 1991-07-08  
Inventor(s): HIRATA RYUICHI; others: 02  
Applicant(s): NIPPON UNICAR CO LTD  
Requested Patent: ☐ [JP3158236](#)  
Application Number: JP19890296097 19891116  
Priority Number(s):  
IPC Classification: B32B25/10; B32B5/08  
EC Classification:  
Equivalents:

---

### Abstract

---

**PURPOSE:**To enhance the flexibility of the laminate concerned by a structure wherein the laminate consists of thermoplastic rubbery elastic layer, which is made of hydrogenated block copolymer and adherent ethylene copolymer, and non-woven fabric, the fibers of which are arranged longitudinally in parallel or in zigzag direction.

**CONSTITUTION:**The laminate concerned is mad of thermoplastic rubber layer consisting of 100 pts.wt. of hydrogenated block copolymer, which is obtained by hydrogenating polymeric block A mainly made of one kind or more of vinyl aromatic compound and polymeric block B mainly made of one kind or more of conjugated diene compound, and 10-150 pts.wt. of ethylene-based copolymer and non-woven fabric. The vinyl aromatic compound used can be selected from among styrene, alpha-methylstyrene, vinyltoluene and the like. The conjugated diene compound before hydrogenated is selected from among butadiene, isoprene, 1,3-pentadiene and the like. Further, the non-woven fabric is fibers such as polypropylene fiber, acrylic fiber, polyester fiber or the like arranged longitudinally in parallel or in zigzag direction. Thus, the laminate having flexibility, waterproofness, dust-proofness and the like is obtained.

---

Data supplied from the esp@cenet database - I2